

NEXT GENERATION POWER ENGINEERING, INC.



OTHER PATENTS PENDING

PATENT #5,765,805

ULTRA COMPACT MARINE 3.5 KW GENERATOR

NEXT Generations UCM1-3.5 is one of the lightest, most compact and efficient gen-sets in its class

- Mid speed operation provides low sound and vibration levels.
- Lower operating speeds to reduce sound levels and increase life expectancy
- Fully fresh water marinized heavy duty Kubota diesel engine for trouble free operation
- Average fuel consumption to just 2/10 GPH.
- Ultra compact size and light-weight construction

IGNITION PROTECTION CERTIFIED

Models can be installed in Gasoline or Diesel Vessels

www.nextgenerationpower.com

FEATURES

- Cupro Nickel Heat Exchanger
- Unit mounted self priming impeller pump
- Stainless steel water cooled exhaust mixer
- Air Cleaner/Intake silencer
- Oil pressure & water temperature safety shutdown
- Extra wide timing drive system
- 12 volt electric fuel pump
- Extra resilient four point isolation mounts
- "Easy Drain" oil change system removable/cleanable oil filter
- Front side service
- Marine grade tinned wire
- Fuel filter
- Main breaker
- Beltguard
- Remote start panel with hour meter and harness

OPTIONS

- Ignition Protection Certification
- Sound Enclosures
- 20' or 30' Wire Harness



30" Long x 18" Wide x 16.5" High

(200 lbs.)



28" Long x 15.5" Wide x 15" High

(160 lbs.)

SPECIFICATIONS

TYPE

Of Cylinders
Bore x Stroke (In)

Displacement (Cu. In.)

SAE net intermittent (HP/rpm)

Combustion System

Compression Ratio Fuel Injection Pump Type

Nozzle Type

Cooling System

Lubricating System

Fuel

Lubricating Oil

Fresh Water capacity
Lubricating Oil Capacity

Starting System

Charging System Fuel Line Diameter

Return Line Diameter Raw Water Diameter

Exhaust Diameter Output Voltage Output AMPS

Output Watts

Horizontal, Water Cooled
 4 Cycle diesel engine

- 1

- 2.95 x 2.76

- 18.86

7/2800Spherical

- 23:1

- Bosch "mini" type

- Bosch "throttle" type

 Fresh Water Heat Exchanger

- Forced by trochoid

pump

- ASTM #2 diesel or

equivalent

 Quality better than API service CE class

- 1.2 qt.

- 1.0 U.S. Quarts

- 12V Battery

- None - 5/16"

- 1/4" - 5/8" - 1 1/2"

- 120/240 - 30/15

- 3500

Specifications Subject to Change Without Notice.

Attention! Bulk Inverter/charges such as those by Trace,
Heart & others have special power requirements.

Please advise before ordering.



1732 St. Johns Bluff Road Jacksonville, FL 32246

1-888-463-9879

Phone (904) 642-8555 / Fax (904) 642-8175 www.nextgenerationpower.com

DEALER: